

Telehandler / Zoom Boom

Used Telehandler Norwalk - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial equipment is commonly used in a variety of industries including agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Popular attachments include a muck grab, bucket, winch or pallet forks. The main telehandler attachment is the pallet forks. They allow the operator to transport loads to and from locations that are considered unreachable with a regular forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Typically, high locations would traditionally require a crane; however, telehandlers can facilitate these tasks easily and efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Using one machine to finish numerous jobs saves storage space, money and time. Telehandlers commonly work alongside a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. The boom acts as a lever when it extends or raises with heavy loads. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. There is a load chart on these machines to determine which tasks can be safely executed by taking the weight, angle and boom height into account. Newer telehandler models rely on computers and sensors to monitor the machine. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. There are many models of telehandlers differing in size, weight, boom designs and reach. Telehandlers that weigh 11,000 pounds or less fall into the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. There are many different applications this machine is suitable for working in. Telehandlers can function as a pick and place unit or a tool carrier. It is commonly utilized in spaces that are tight and cramped. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers come with crab steering or two or four-wheel drive options. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for

moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering enhances the units' maneuverability while allowing each set of wheels to move forty-five degrees to the right or left. Compact telehandlers have varying cab environments. On entry-level models, there is a rollover cage for added safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. Operators enjoy spacious accommodation for ultimate comfort. Additional features such as cup holders, air conditioning, tilt steering, suspension seats and satellite radio are all options. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact units are more commonly utilized for ground engaging jobs. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. Light and heavy-duty buckets can be used to move items, augers can plant trees or drill holes, rotating and side-shifting fork carriages facilitate pick-and-place, truss booms are in place for extending reach, sweeping brooms and crane hooks are other popular attachments. Skid steer options are made for compact telehandler designs and ultimate versatility.